

Performance Comparison Of Reusable Launch Vehicles

Probabilistic Performance Comparison of RBCC- and TBCC-based Reusable Launch Vehicles with Enhancing Technologies
 From Diagnostics & Prognostics to Structural Health Management : Proceedings of the 4th International Workshop on Structural Health Monitoring, Stanford University, Stanford, CA, September 15-17, 2003
 Space Launch Initiative
 Performance Comparison of Reusable Launch Vehicles
 Summary of a Conference
 Department of Defense Appropriations for Fiscal Year 1971, Hearings Before ..., 91-2
 New World Vistas
 Volume-II: Nano to Macro
 Air and Space Power for the 21st Century : Materials Volume
 Space Shuttle Hypersonic Aerodynamic and Aerothermodynamic Flight Research and the Comparison to Ground Test Results
 Dictionary of Space Technology
 A Damage Resistance Comparison Between Candidate Polymer Matrix Composite Feedline Materials
 Reusable Launch Vehicle
 Proceedings of American Astronautical Society Seventh Goddard Memorial Symposium, March 4-5, 1969, Washington, D. C.
 NASA Scientific and Technical Reports
 Department of Defense Appropriations for Fiscal Year 1971
 Hearings Before the Subcommittee of the Committee on Appropriations, United States Senate, Ninety-first Congress, Second Session
 Department of the Air Force
 Analysis of Factors Affecting the Performance of Rlv Thrust Cell Liners
 A History of the Johnson Space Center
 International Aerospace Abstracts
 Macromolecular Symposia, No. 199
 Feasibility of Space Disposal of Radioactive Nuclear Waste
 NASA Technical Note
 Air Traffic Management and Conflict Analysis for Reusable Launch Vehicles
 1970 NASA Authorization, Hearings...
 Scientific and Technical Aerospace Reports
 Reusable Launch Vehicles and Space Operations
 Review and Assessment
 1970 NASA Authorization
 Technical summary. II
 Aerospace Environmental Technology Conference
 Polycondensation 2002
 Hearings
 Second Aerospace Environmental Technology Conference
 A Selected Listing
 Structural Health Monitoring 2003
 Reducing the Cost of Space Transportation
 39th AIAA/ASME/SAE/ASEE Joint Propulsion Conference & Exhibit July 20-23, 2003, Huntsville, Alabama: 03-5000 - 03-5049

Performance Comparison Of Reusable Launch Vehicles

Downloaded from ftp.wtvq.com by guest

YOUNG SIMS

Probabilistic Performance Comparison of RBCC- and TBCC-based Reusable Launch Vehicles with Enhancing Technologies Routledge
 The international symposium "POLYCONDENSATION 2002" (15-18 September, in Hamburg, Germany) was the 4th meeting of a series launched in Paris 1996. This symposium covered topics such as: New theories New synthetic methods Block copolymers Hyperbranched polymers Liquid crystalline polymers Properties and application This book contains (oral) contributions of the symposium.
From Diagnostics & Prognostics to Structural Health Management : Proceedings of the 4th International Workshop on Structural Health Monitoring, Stanford University, Stanford, CA, September 15-17, 2003 National Academies Press
 As part of NASAs focused technology programs for future reusable launch vehicles, a task is underway to study the feasibility of using the polymer matrix composite feedlines instead of metal ones on propulsion systems. This is desirable to reduce weight and manufacturing costs. The task consists of comparing several prototype composite feedlines made by various methods. These methods are electron-beam curing, standard hand lay-up and autoclave cure, solvent assisted resin transfer molding, and thermoplastic tape laying. One of the critical technology drivers for composite components is resistance to foreign objects damage. This paper presents results of an experimental study of the damage resistance of the candidate materials that the prototype feedlines are manufactured from. The materials examined all have a 5-harness weave of IM7 as the fiber constituent

(except for the thermoplastic, which is unidirectional tape laid up in a bidirectional configuration). The resin tested were 977-6, PR 520, SE-SA-1, RS-E3 (e-beam curable), Cycom 823 and PEEK. The results showed that the 977-6 and PEEK were the most damage resistant in all tested cases. Nettles, A. T. Marshall Space Flight Center
 COMPOSITE MATERIALS; CURING; DAMAGE; TECHNOLOGY ASSESSMENT; HARNESSSES; MANUFACTURING; POLYMER MATRIX COMPOSITES; AUTOCLAVES; COSTS; ELECTRON BEAMS; FEED SYSTEMS; LAY-UP; PROPULSION SYSTEM CONFIGURATIONS; PROPULSION SYSTEM PERFORMANCE; PROTOTYPES; RESIN TRANSFER MOLDING; REUSABLE LAUNCH VEHICLES; THERMOPLASTICITY; WEIGHT REDUCTION
 Space Launch Initiative Springer Nature
 Performance Comparison of Reusable Launch Vehicles
 Probabilistic Performance Comparison of RBCC- and TBCC-based Reusable Launch Vehicles with Enhancing Technologies
 Evaluation of Monopropellants for Reusable Launch Vehicles
Performance Comparison of Reusable Launch Vehicles Independently Published
 Important new information on sensors, monitoring, prognosis, networking, and planning for safety and maintenance.
 Summary of a Conference National Academies Press
 As a result of technological progress, we are now on verge of developing cost-effective reusable launch vehicles (RLV) for space. This study reviews the strategic implications of the emerging vision within the U.S. Department of Defense for using these vehicles. Although the U.S. Air Force is making the transition to a force that relies increasingly on space, the best path does not necessarily involve replicating the traditional air missions in space. This study of potential missions for RLVs concludes that, while these are capable of numerous missions (e.g., reconnaissance, global strike, cargo and

personnel transport), the most important mission for the immediate future for both the U.S. military and commercial firms is in the area of traditional spacelift. The two broad conclusions that emerge from this study are that the U.S. military should move away from the spacelift business by obtaining spacelift through commercially procured launch services, and second, that the U.S. military should not develop militarized RLVs that are designed to perform the traditional air operations in space.

[Department of Defense Appropriations for Fiscal Year 1971, Hearings Before ... 91-2](#) John Wiley & Sons

On June 15, 2011, the Air Force Space Command established a new vision, mission, and set of goals to ensure continued U.S. dominance in space and cyberspace mission areas. Subsequently, and in coordination with the Air Force Research Laboratory, the Space and Missile Systems Center, and the 14th and 24th Air Forces, the Air Force Space Command identified four long-term science and technology (S&T) challenges critical to meeting these goals. One of these challenges is to provide full-spectrum launch capability at dramatically lower cost, and a reusable booster system (RBS) has been proposed as an approach to meet this challenge. The Air Force Space Command asked the Aeronautics and Space Engineering Board of the National Research Council to conduct an independent review and assessment of the RBS concept prior to considering a continuation of RBS-related activities within the Air Force Research Laboratory portfolio and before initiating a more extensive RBS development program. The committee for the Reusable Booster System: Review and Assessment was formed in response to that request and charged with reviewing and assessing the criteria and assumptions used in the current RBS plans, the cost model methodologies used to frame the RBS business case, and the technical maturity and development plans of key elements critical to RBS implementation. The committee consisted of experts not connected with current RBS activities who have significant expertise in launch vehicle design and operation, research and technology development and implementation, space system operations, and cost analysis. The committee solicited and received input on the Air Force launch requirements, the baseline RBS concept, cost models and assessment, and technology readiness. The committee also received input from industry associated with RBS concept, industry independent of the RBS concept, and propulsion system providers which is summarized in Reusable Booster System: Review and Assessment.

[New World Vistas](#) Createspace Independent Publishing Platform

This volume presents selected papers from the 7th International Congress on Computational Mechanics and Simulation held at IIT Mandi, India. The papers discuss the development of mathematical models representing physical phenomena and applying modern computing methods and simulations to analyse them. The studies cover recent advances in the fields of nano mechanics and biomechanics, simulations of multiscale and multiphysics problems, developments in solid mechanics and finite element method, advancements in computational fluid dynamics and transport phenomena, and applications of computational mechanics and techniques in emerging areas. The volume will be of interest to researchers and academics from civil engineering, mechanical engineering, aerospace engineering, materials engineering/science, physics, mathematics and other disciplines.

Volume-II: Nano to Macro Performance Comparison of Reusable Launch Vehicles Probabilistic Performance Comparison of RBCC- and TBCC-based Reusable Launch Vehicles with Enhancing Technologies Evaluation of Monopropellants for Reusable Launch Vehicles Previously, the Air Force has been investigating high performance salt-based, liquid monopropellants for low thrust spacecraft applications. The focus of this effort has been on finding a reduced toxicity monopropellant with a predicted density performance impulse greater than 50% over hydrazine. During this same period of time, NASA has been investigating reusable launch vehicle (KLV) concepts and has considered using monopropellants in this application. Anticipating a possible RLV payoff, NASA and the Air Force are working on a trade study to gauge the potential applicability of the salt-based monopropellants in booster applications. This study will include a performance comparison of salt-based monopropellants; a list of minimum safety, hazard, and physical property requirements based on operational and logistical support environments for an RLV. Reusable Booster System Review and Assessment Previously, the Air Force has been investigating high performance salt-based, liquid monopropellants for low thrust spacecraft applications. The focus of this effort has been on finding a reduced toxicity monopropellant with a predicted density performance impulse greater than 50% over hydrazine. During this same period of time, NASA has been investigating reusable launch vehicle (KLV) concepts and has considered using monopropellants in this application. Anticipating a possible RLV payoff, NASA and the Air Force are working on a trade study to gauge the potential applicability of the salt-based monopropellants in booster applications. This study will include a performance comparison of salt-based monopropellants; a list of minimum safety, hazard, and physical property requirements based on operational and logistical support environments for an RLV.

[Air and Space Power for the 21st Century : Materials Volume](#) DEStech Publications, Inc

Originally published in 1981, the completely revised and updated second edition of the Dictionary of Space Technology illustrates the advances of the last 20 years and makes accessible nearly every word, concept, and event relating to this branch of science. It guides lay persons and professionals alike through humankind's activities in space, the beginnings of our extraterrestrial society, and the increasingly important role of space sciences in everyday life. Defines more than 1,500 terms, including: science basics; historic events; defence and armed forces terminology; and planetary sciences. Enhanced by more than 175 photographs and drawings, this Dictionary covers the past, the present and the future of space, space flight, and space technology.

Space Shuttle Hypersonic Aerodynamic and Aerothermodynamic Flight Research and the Comparison to Ground Test Results

Independently Published

The design of the next generation of space access vehicles has led to a unique flight test that blends the space and flight research worlds. The new vehicle designs, such as the X-33 vehicle and Reusable Launch Vehicle (RLV) are powered by linear aerospike rocket engines. Conceived of in the 1960's, these aerospike engines have yet to be flown, and many questions remain regarding aerospike engine performance and efficiency in flight. To provide some of these data before flying on the X-33 vehicle and the RLV, a spacecraft rocket engine had been flight-tested atop the NASA SR-71 aircraft as the Linear Aerospike SR-71 Experiment (LASRE). A 20 percent-scale, semispan model of the X-33 vehicle, the aerospike engine, and all the required fuel and oxidizer tanks and propellant feed systems have been mounted atop the SR-71 airplane for this experiment. A major technical objective of the LASRE flight test is to obtain installed-engine performance flight data for comparison to wind-tunnel results and for the development of computational fluid dynamics-based design methodologies. The ultimate goal of firing the aerospike rocket engine in flight is still forthcoming. An extensive design and development phase of the experiment hardware has been completed, including approximately 40 ground tests. Five flights of the LASRE and firing the rocket engine using inert liquid nitrogen and helium in place of liquid oxygen and hydrogen have been successfully completed.

[Dictionary of Space Technology](#)

The key to opening the use of space to private enterprise and to broader public uses lies in reducing the cost of the transportation to space. More routine, affordable access to space will entail aircraft-like quick turnaround and reliable operations. Currently, the space Shuttle is the only reusable launch vehicle, and even parts of it are expendable while other parts require frequent and extensive refurbishment. NASA's highest priority new activity, the Reusable Launch Vehicle program, is directed toward developing technologies to enable a new generation of space launchers, perhaps but not necessarily with single stage to orbit capability. This book assesses whether the technology development, test and analysis programs in propulsion and materials-related technologies are properly constituted to provide the information required to support a December 1996 decision to build the X-33, a technology demonstrator vehicle; and suggest, as appropriate, necessary changes in these programs to ensure that they will support vehicle feasibility goals.

A Damage Resistance Comparison Between Candidate Polymer Matrix Composite Feedline Materials

The reusable launch vehicle (RLV) thrust cell liner, or thrust chamber, is a critical component of the Space Shuttle Main Engine (SSME). It is designed to operate in some of the most severe conditions seen in engineering practice. This requirement, in conjunction with experimentally observed 'dog-house' failure modes characterized by bulging and thinning of the cooling channel wall, provides the motivation to study the factors that influence RLV thrust cell liner performance. Factors or parameters believed to be directly related to the observed characteristic deformation modes leading to failure under in-service loading conditions are identified, and subsequently investigated using the cylindrical version of the higher-order theory for functionally graded materials in conjunction with the Robinson's unified viscoplasticity theory and the power-law creep model for modeling the response of the liner's constituents. Configurations are analyzed in which specific modifications in cooling channel wall thickness or constituent materials are made to determine the influence of these parameters on the deformations resulting in the observed failure modes in the outer walls of the cooling channel. The application of thermal barrier coatings and functional grading are also investigated within this context. Comparison of the higher-order theory results based on the Robinson and power-law creep model predictions has demonstrated that, using the available material parameters, the power-law creep model predicts more precisely the experimentally observed deformation leading to the 'dog-house' failure mode for multiple short cycles, while also providing much improved computational efficiency. However, for a single long cycle, both models predict virtually identical deformations. Increasing the power-law creep model coefficients produces appreciable deformations after just one long cycle that would normally be obtained after multiple cycles, thereby enhancing the efficiency of the anal

[Reusable Launch Vehicle](#)

This report documents recent improvements to the acoustic and thermal control systems of the Thermal Acoustic Fatigue Apparatus (TAFA), a progressive wave tube test facility at the NASA Langley Research Center, Hampton, Virginia. A brief summary of past acoustic performance is given first to serve as a basis for comparison with the new performance data using a multiple-input, closed-loop, narrow-band controller. Performance data in the form of test section acoustic power spectral densities and coherence are presented in three of six facility configurations for a variety of input spectra. Tested spectra include uniform, two cases of pink noise, three cases of narrow-band random, a simulated launch payload bay environment for an expendable launch vehicle, and a simulated external acoustic load for the aft section of a reusable launch vehicle. In addition, a new closed-loop temperature controller and thermocouple data acquisition system are described. Rizzi, Stephen A. Langley Research Center PERFORMANCE TESTS; TEST CHAMBERS; TEST FACILITIES; RESEARCH AND DEVELOPMENT; EXPERIMENTATION; RESEARCH FACILITIES; LAUNCHING; SPECTRA; SIMULATION **Proceedings of American Astronautical Society Seventh Goddard Memorial Symposium, March 4-5, 1969, Washington, D. C.**

NASA Scientific and Technical Reports

Department of Defense Appropriations for Fiscal Year 1971

Hearings Before the Subcommittee of the Committee on Appropriations, United States Senate, Ninety-first Congress, Second Session

Department of the Air Force

Analysis of Factors Affecting the Performance of Rlv Thrust Cell Liners